

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Substance
Substance name	: NAF S 125 (HFC-125)
Chemical name	: pentafluoroethane: 206-557-8
EC no	: 206-557-8
CAS No	: 354-33-6
REACH registration No	: 01-2119485636-25

1.2 Relevant identified uses of the substance or mixture and uses advised against**1.2.1 Relevant identified uses**

Use of the substance/mixture	: Extinguishing/Inerting agent
------------------------------	--------------------------------

1.2.2. Uses advised against

No additional information available

1.3 Details of the supplier of the safety data sheet

SAFETY HI-TECH GLOBAL LLC
1000 N West Street, Suite 1200
Wilmington, DE 1980 – USA
T +1 302 295 48 08 – E mail@sht-global.com

1.4 Emergency telephone number

Emergency number	: +1 302 295 48 08
------------------	--------------------

SECTION 2: Hazards Identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Liquefied gas	: H280
Full text of hazard classes and H-statements	: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP)



GHS04

Signal word (CLP)	: Warning
Hazard statements (CLP)	: H280-Contains gas under pressure; may explode if heated
Precautionary statements (CLP)	: P410+P403-Protect from sunlight. Store in a well-ventilated place
Extra phrases	: Greenhouse fluorinated gas falling within Kyoto Protocol (GWP=3500)



2.3. Other hazards

Other hazards not contributing to the classification

: May cause suffocation by reducing oxygen available for breathing.
Contact with the liquid may cause cold burns/frostbite.

SECTION 3: Composition/Information on Ingredients

3.1. Substance

Name : NAF S 125 (HFC-125)
CAS No : 354-33-6
EC No : 206-557-8

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008
1,1,1,2,3,3,3-heptafluoropropane	(CAS No) 354-33-6 (EC no) 206-557-8 (REACH-no) 01-2119485636-25	> 99	Liquefied gas, H280

Full text of H-statements: see section 16

3.2. Mixture

Not applicable

SECTION 4: First Aid Measures

4.1. Description of first aid measures

First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.
First-aid measures after skin contact : In the event of contact with the liquid: treat resulting frostbite as a burn. Immediately remove contaminated clothing or footwear. Immediately rinse with plenty of water. If skin burns appear, call a doctor immediately.
First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Consult an eye specialist immediately.
First-aid measures after ingestion : Not specifically applicable (gas).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : CNS depression. Narcosis. Cardiac disorders. Lack of oxygen: risk of death.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Fire-fighting Measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray, Foam, Carbon Dioxide, Chemical Powder.

5.2. Special hazards arising from the substance or mixture

Explosion hazard : Heating will cause a rise in pressure with a risk of bursting. Thermal decomposition can lead to the release of irritating gases and vapors including Hydrogen fluoride. Carbon oxides (CO, CO₂).

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Evacuate the danger area. Do not breathe smoke. Stop the leak. In closed premises: Ventilate or wear self-contained breathing apparatus (risk of asphyxia). Remove all sources of ignition. Do not smoke.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Other information : Mechanically ventilate the spillage area.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Precautions for safe handling : Ventilation. Remove all sources of ignition. Use personal protective equipment as required.
Hygiene measures : Do not drink, eat or smoke in the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in original container.
Incompatible materials : Alkali Metals. Alkaline earth metals. Strong oxidizing agents
Storage temperature : <50°C
Packaging materials : Recommended materials: Carbon steel, Aluminum.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure Controls/Personal Protection and Storage

8.1. Control parameters

NAF S 125 - HFC 125 (354-33-6)
EU : No specific limit

pentafluoroethane (354-33-6)
 DNEL/DMEL (Workers) :
 Long-term - systemic effects, inhalation 16444 mg/m³
 DNEL/DMEL (General population) :
 Long-term - systemic effects, inhalation 1753 mg/m³
 PNEC (Water) :
 PNEC aqua (freshwater) 0.1 mg/l
 PNEC (Sediment) :
 PNEC sediment (freshwater) 1 mg/kg dwt
 PNEC (STP) :
 PNEC sewage treatment plant 1.73 mg/l

8.2. Exposure controls

Hand protection : Leather protective gloves. Nitrile-rubber protective gloves. VITON gloves
 Eye protection : Safety glasses with side shields
 Skin and body protection : Majority cotton protective clothing
 Respiratory protection : In the event of insufficient ventilation: Gas mask with filter type AX. In a confined area: Self-Contained breathing apparatus

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
 Appearance : Liquefied gas
 Color : Colorless
 Odor : Citrus
 Odor threshold : No data available
 pH : Not applicable
 Relative evaporation rate (butyl acetate=1) : No data available
 Melting point : -103 °C
 Freezing point : No data available
 Boiling point : -48.3 °C
 Flash point : None
 Auto-ignition temperature : Not determined
 Decomposition temperature : No data available
 Flammability (solid, gas) : Not flammable
 Vapor pressure : 13.76 hPa (20°C)
 Vapor pressure at 50 °C : No data available
 Vapor density at 20 °C : 4.1
 Relative density : No data available
 Density : No data available
 Solubility : Water: 430 mg/l (25°C)
 Log Pow : No data available
 Viscosity, kinematic : No data available
 Viscosity, dynamic : No data available
 Explosive properties : Not explosive material according to EC criteria
 Oxidizing properties : Non-oxidizing material according to EC criteria
 Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and Reactivity

10.1. Reactivity

Contains gas under pressure; may explode if heated.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous polymerization.

10.4. Conditions to avoid

Ignition sources. Heat or source of heat. Avoid contact with hot surfaces.

10.5. Incompatible materials

Strong oxidizing agents. alkali metals. Alkaline earth metals.

10.6. Hazardous decomposition products

On thermal decomposition (pyrolysis), releases: Carbon oxides (CO, CO₂), Hydrogen fluoride.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Additional information	: Asphyxiating
pentafluoroethane (354-33-6)	
LC50 inhalation rat (ppm)	> 800000 ppm/4h
Skin corrosion/irritation	: Not classified - pH: Not applicable
Additional information	: Contact with the liquid may cause cold burns/frostbite
Serious eye damage/irritation	: Not classified - pH: Not applicable
Additional information	: Contact with the liquefied gas may cause severe ocular lesions
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exp.)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological Information

12.1. Toxicity

pentafluoroethane (354-33-6)	
LC50 fish 1	> 81.8 mg/l (Oncorhynchus mykiss)

EC50 Daphnia 1
 EC50 72h algae (1)

 > 97.9 mg/l (Daphnia magna)
 > 118 mg/l (Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

pentafluoroethane (354-33-6)
 Persistence and degradability

Not readily biodegradable. 5 % biodegradation after 28 days.

12.3. Bio accumulative potential

pentafluoroethane (354-33-6)
 Log Pow

1.34

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

pentafluoroethane (354-33-6)

: This substance/mixture does not meet the PBT and vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Other adverse effects

: Ozone depletion factor ODP (R-11=1) = 0. Total global warming potential (GWP): 3500

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Waste disposal recommendations

: Methods of disposal of packaging. Reuse or recycle following decontamination. Destroy at an authorized site.

Additional information

: The user's attention is drawn to the possible existence of specific European, national or local regulations regarding disposal.

SECTION 14: Transport Information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA
14.1. UN number		
3220	3220	3220
14.2. UN proper shipping name		
(Refrigerant Gas R 125) Pentafluoroethane	Pentafluoroethane (Pentafluoroethane Gas R 125)	(Refrigerant Gas R 125) Pentafluoroethane
Transport Document Description		
UN 3220 Pentafluoroethane (Refrigerant Gas R 125), 2.2, (C/E)	UN 3220 Pentafluoroethane (Refrigerant Gas R 125), 2.2	UN 3220 Pentafluoroethane, 2.2
14.3. Transport hazard class(es)		
2.2	2.2	2.2


14.4. Packing group

Not applicable

14.5. Environmental hazards

Dangerous for the environment: No

No supplementary information available



Not applicable

Dangerous for the environment: No Marine pollutant : No



Not applicable

Dangerous for the environment : No

14.6. Special precautions for user
Overland transport

Classification code (ADR)	: 2A
Special provisions (ADR)	: 662
Limited quantities (ADR)	: 120ml
Tank code (ADR)	: PxBN(M)
Transport category (ADR)	: 3
Hazard identification number (Kemler No.)	: 20
Tunnel restriction code (ADR)	: C/E
EAC code	: 2T

Transport by sea

Limited quantities (IMDG)	: 120 ml
EmS-No. (Fire)	: F-C
EmS-No. (Spillage)	: S-V

Air transport

PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 200
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 200
CAO max net quantity (IATA)	: 150kg

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory Information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
15.1.1. EU-Regulations

No REACH Annex XVII restrictions
 HFC 125 is not on the REACH Candidate List
 HFC 125 is not on the REACH Annex XIV List

Other information, restriction and prohibition regulations	: Regulation (EC) No 517/2014
--	-------------------------------

15.1.2. National regulations

Ensure all national/local regulations are observed

15.2. Chemical safety assessment

Not applicable

SECTION 16: Other Information



NAF[®] S 125 (HFC-125) Material Safety Data Sheet

Made in accordance with according to Regulation (EC) No. 1907/2006 (REACH)
with its amendment Regulation (EU) 2015/830

Date of issue: 12/23/2018 - Version: 1.1 - Supersedes: Version 1.0

Indication of changes:

All chapters have been modified since the previous version.

Other information

: For more information regarding the use of this product, please refer to our technical information or contact the sales department in your region.

Full text of H- and EUH-statements:

Liquefied gas
H280

Gases under pressure: Liquefied gas
Contains gas under pressure; may explode if heated